



| MOTOR               |                     |                     |
|---------------------|---------------------|---------------------|
| ANVEND              |                     | KLIMA               |
| Normal              |                     | Moderat             |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3 |
| <b>Tornado</b>      | <b>Scoosynth</b>    | <b>Maestrol</b>     |

| GEAR MANUEL 6<br>Kapacitet: 0,9 liter |                       |                     |
|---------------------------------------|-----------------------|---------------------|
| ANVEND                                |                       | KLIMA               |
| Normal                                |                       | Moderat             |
| PRODUKTANBEFALING 1                   | PRODUKTANBEFALING 2   | PRODUKTANBEFALING 3 |
| <b>Expulsa RR 10W-40</b>              | <b>Expulsa 10W-40</b> | <b>HDX 10W-40</b>   |

*Skift alle 29 liter forbrugt brændstof*

| HYDRAULISK BREMSESYSTEM<br>Kapacitet: 0-0 liter (Imellem min. og max.) |                           |                         |
|------------------------------------------------------------------------|---------------------------|-------------------------|
| ANVEND                                                                 |                           | KLIMA                   |
| Normal                                                                 |                           | Moderat                 |
| PRODUKTANBEFALING 1                                                    | PRODUKTANBEFALING 2       | PRODUKTANBEFALING 3     |
| <b>Drauliquid-LV Super DOT 4</b>                                       | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b> |

*Skift alle 24 måneder*

| HYDRAULISK KOBLINGSSYSTEM<br>Kapacitet: 0-0 liter (Imellem min. og max.) |  |  |
|--------------------------------------------------------------------------|--|--|
|--------------------------------------------------------------------------|--|--|

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

| KØLESYSTEM<br>Kapacitet: 0-0 liter (Imellem min. og max.) |  |         |
|-----------------------------------------------------------|--|---------|
| ANVEND                                                    |  | KLIMA   |
| Normal                                                    |  | Moderat |
| PRODUKTANBEFALING 1                                       |  |         |
| <b>Coolant SP 12 EVO</b>                                  |  |         |

*Skift alle 24 måneder*

# GAS GAS EC EC 300 (2004-2006)



## FORGAFFEL

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Perlus H 32**

*Skift alle 12 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*