

HARLEY-DAVIDSON DYNA FLD/FXD FXE/F FAT BOB 1340 (1980-1985)



MOTOR

Kapacitet: 2,8 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Kontroller alle 2500 km, skift alle 5000 km

ANVEND

Acceptabel

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 15W-40

PRODUKTANBEFALING 2

Bi-Turbo 20W-50

ANVEND

Acceptabel

KLIMA

Koldt

PRODUKTANBEFALING 1

Emperol 10W-40

GEAR 5

Kapacitet: 0,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 2500 km, skift alle 5000 km

PRIMÆRE KÆDEDREV

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 10W-40

PRODUKTANBEFALING 2

Expulsa 10W-40

Kontroller alle 2500 km, skift alle 5000 km

HYDRAULISK BREMSESYSTEM

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

HARLEY-DAVIDSON DYNA FLD/FXD FXE/F FAT BOB 1340 (1980-1985)



FORGAFFEL

Kapacitet: 0,79 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

Skift alle 10000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.