

HARLEY-DAVIDSON SOFTAIL FLS/FXS FXSTB SOFTAIL NIGHT TRAIN (1997-1999)



MOTOR Evolution
Kapacitet: 2,84 liter

ANVEND	KLIMA
Normal (alternativ)	Moderat

PRODUKTANBEFALING 1		
Bi-Turbo 20W-50		

Kontroller alle 4000 km, skift alle 8000 km/ 12 måneder

ANVEND	KLIMA
Normal (foretrukne)	Middelhavsagtigt

PRODUKTANBEFALING 1		
Bi-Turbo 20W-50		

Kontroller alle 4000 km, skift alle 8000 km/ 12 måneder

ANVEND	KLIMA
Acceptabel	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Bi-Turbo 15W-40	Bi-Turbo 20W-50	

ANVEND	KLIMA
Acceptabel	Koldt

PRODUKTANBEFALING 1		
Emperol 10W-40		

GEAR 5
Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 4000 km/ 1 måneder, skift alle 8000 km

PRIMÆRE KÆDEDREV
Kapacitet: 0,77 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Expulsa RR 10W-40	Expulsa 10W-40	

Kontroller alle 1 måneder, skift alle 8000 km

HARLEY-DAVIDSON SOFTAIL FLS/FXS FXSTB SOFTAIL NIGHT TRAIN (1997-1999)



HYDRAULISK BREMSESYSTEM

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.