

HARLEY-DAVIDSON SOFTAIL FLS/FXS FXSTS/I SPRINGER SOFTAIL (2000-2005)



MOTOR Twin Cam 88B
Kapacitet: 3,3 liter

ANVEND	KLIMA
Normal (alternativ)	Moderat

PRODUKTANBEFALING 1		
Bi-Turbo 20W-50		

Skift alle 8000 km

ANVEND	KLIMA
Normal (foretrukne)	Middelhavsagtigt

PRODUKTANBEFALING 1		
Bi-Turbo 20W-50		

Skift alle 8000 km

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1		
Bi-Turbo 20W-50		

Skift alle 1600 km

ANVEND	KLIMA
Acceptabel	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Bi-Turbo 15W-40	Bi-Turbo 20W-50	

ANVEND	KLIMA
Acceptabel	Koldt

PRODUKTANBEFALING 1		
Emperol 10W-40		

GEAR 5
Kapacitet: 0,59-0,71 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Bi-Turbo 20W-50		

Skift alle 32000 km

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Bi-Turbo 20W-50		

Skift alle 800 km

HARLEY-DAVIDSON SOFTAIL FLS/FXS FXSTS/I SPRINGER SOFTAIL (2000-2005)



PRIMÆRE KÆDEDREV

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 16000 km

HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0,35 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.