

HARLEY-DAVIDSON TOURING FLH/FLT/FLR FLHR ROAD KING SHRINE FW4 (2011-2012)



MOTOR Twin Cam 96
Kapacitet: 3,79 liter

ANVEND	KLIMA
Normal (foretrukne)	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 8000 km

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 1600 km

ANVEND	KLIMA
Kort distance	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 2400 km

GEAR 6
Kapacitet: 0,95 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 32000 km

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 1600 km

HARLEY-DAVIDSON TOURING FLH/FLT/FLR FLHR ROAD KING SHRINE FW4 (2011-2012)



PRIMÆRE KÆDEDREV

Kapacitet: 1,32 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 16000 km

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 1600 km

HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 8000 km, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.