

HARLEY-DAVIDSON VRSC VRS VRSCR STREET ROD HCG (2007-2008)



MOTOR/GEARKASSE Revolution 76

Kapacitet: 4,3 liter, Kapacitet: 4,7 liter (Overhaling kapacitet)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 8000 km

ANVEND	KLIMA
Normal (alternativ)	Moderat

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 8000 km

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 1600 km

ANVEND	KLIMA
Acceptabel	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 15W-40

PRODUKTANBEFALING 2

Bi-Turbo 20W-50

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 8000 km, skift alle 24 måneder

HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 8000 km, skift alle 24 måneder

HARLEY-DAVIDSON VRSC VRS VRSCR STREET ROD HCG (2007-2008)



KØLESYSTEM

Kapacitet: 2,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 48000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.