

# HERKULES INTERCEPTOR ATV 300

## INTERCEPTOR (2009 OG EFTER)



### MOTOR/GEARKASSE

Kapacitet: 1,6 liter (Servicepåfyldning), Kapacitet: 2 liter (Tør efterfyld)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2   |  |
|--------------------------|-----------------------|--|
| <b>Expulsa RR 10W-40</b> | <b>Expulsa 10W-40</b> |  |

Skift alle 1000 km/ 100 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2   |  |
|--------------------------|-----------------------|--|
| <b>Expulsa RR 10W-40</b> | <b>Expulsa 10W-40</b> |  |

Skift alle 150 km/ 20 timer

### HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |  |
|----------------------------------|---------------------------|--|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |  |

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.