

HONDA MUV MUV 700 / BIG RED (2009-2013)



MOTOR/GEARKASSE

Kapacitet: 2,9 liter (Servicepåfyldning), Kapacitet: 4,1 liter (Tør efterfyld), Filterkapacitet: 0,2 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Expulsa RR 10W-40	Expulsa 10W-40

Skift alle 1000 km/ 12 måneder/ 100 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Expulsa RR 5W-40	

Skift alle 1000 km/ 12 måneder/ 100 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Expulsa RR 10W-40	Expulsa 10W-40

Skift alle 150 km/ 1 måneder/ 20 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Expulsa RR 5W-40	

Skift alle 150 km/ 1 måneder/ 20 timer

DIFFERENTIALE BAG

Kapacitet: 465 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
SP Gear 5015	SP Gear 1071

Skift alle 24 måneder

DIFFERENTIALE FOR

Kapacitet: 665 cm3

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
SP Gear 5015	SP Gear 1071

Skift alle 24 måneder

HONDA MUV MUV 700 / BIG RED (2009-2013)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Skift alle 24 måneder

KØLESYSTEM

Kapacitet: 3,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.