

HONDA TRX TRX 450 R/ER (2006-2009)



MOTOR

Kapacitet: 0,69 liter (Servicepåfyldning), Kapacitet: 0,85 liter (Tør efterfyld)

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40

Skift alle 1000 km/ 12 måneder/ 100 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Expulsa RR 5W-40		

Skift alle 1000 km/ 12 måneder/ 100 timer

ANVEND		KLIMA
Første Service		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40

Skift alle 150 km/ 1 måneder/ 20 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1		
Expulsa RR 5W-40		

Skift alle 150 km/ 1 måneder/ 20 timer

GEAR 5

Kapacitet: 0,68 liter (Servicepåfyldning), Kapacitet: 0,8 liter (Tør efterfyld)

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40

Skift alle 1000 km/ 12 måneder/ 100 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Expulsa RR 5W-40		

Skift alle 1000 km/ 12 måneder/ 100 timer

HONDA TRX TRX 450 R/ER (2006-2009)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 24 måneder

KØLESYSTEM

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.