

HONDA VFR VFR 800 A/ABS (2002-2006)



MOTOR/GEARKASSE

Kapacitet: 3,1 liter, Kapacitet: 3,8 liter (Overhaling kapacitet), Filterkapacitet: 0,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Expulsa 10W-40

Skift alle 12000 km/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Expulsa 10W-40

Skift alle 1000 km

HYDRAULISK BREMSESYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 6000 km/ 6 måneder, skift alle 18000 km/ 24 måneder

HYDRAULISK KOBLINGSSYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 6000 km/ 6 måneder, skift alle 18000 km/ 24 måneder

KØLESYSTEM

Kapacitet: 2,92 liter (Radiator + motor), Kapacitet: 0,9 liter (Reservetank), Kapacitet: 3,82 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 12000 km/ 12 måneder, skift alle 36000 km/ 24 måneder

HONDA VFR VFR 800 A/ABS (2002-2006)



FORGAFFEL

Kapacitet: 0,54 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 12000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.