

HOREX VR6 VR6 CLASSIC (2013-2014)



MOTOR/GEARKASSE VR6

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Expulsa RR 15W-50		

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid DOT 5.1	Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4

HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid DOT 5.1	Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4

KØLESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

FORGAFFEL

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.