

HUSQVARNA FE FE 250 (2014-2014)



MOTOR/GEARKASSE

Kapacitet: 1,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-50

Skift alle 15 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-50

Skift alle 1 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 5.1

PRODUKTANBEFALING 2

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 3

Drauliquid-S DOT 4

Skift alle 12 måneder

HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 5.1

PRODUKTANBEFALING 2

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 3

Drauliquid-S DOT 4

Skift alle 12 måneder

KØLESYSTEM

Kapacitet: 1,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Skift alle 12 måneder

FORGAFFEL WP 4860 4CS

Kapacitet: 635 cm3 (hvert ben)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

HUSQVARNA FE FE 250 (2014-2014)



STØDDÆMPER BAG WP 5018 BAVP DCC

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.