

HYOSUNG RT RT 125 D (2007 OG EFTER)



MOTOR/GEARKASSE

Kapacitet: 0,95 liter (Servicepåfyldning), Kapacitet: 1,2 liter (Tør efterfyld), Filterkapacitet: 0,1 liter

ANVEND		KLIMA
Normal		Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

Skift alle 4000 km

ANVEND		KLIMA
Første Service		Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

Skift alle 1000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Kontroller alle 4000 km, skift alle 24 måneder

FORGAFFEL

Kapacitet: 215 cm³ (hvert ben)

ANVEND		KLIMA
Normal		Moderat

PRODUKTANBEFALING 1		
Fork Oil RR 5		

Kontroller alle 4000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.