

INDIAN CHIEF/VINTAGE CHIEF STANDARD (2009-2010)



MOTOR 105

Kapacitet: 3,31 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 15W-50

PRODUKTANBEFALING 2

Bi-Turbo 20W-50

Skift alle 8000 km

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 15W-50

PRODUKTANBEFALING 2

Bi-Turbo 20W-50

Skift alle 800 km

ANVEND

Andet skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 15W-50

PRODUKTANBEFALING 2

Bi-Turbo 20W-50

Skift alle 4000 km

GEAR 6

Kapacitet: 0,6-0,72 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 8000 km

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 800 km

INDIAN CHIEF/VINTAGE CHIEF STANDARD

(2009-2010)

**HOVEDDREV**

Kapacitet: 0,59-0,65 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 8000 km*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 800 km***HYDRAULISK BREMSESYSTEM BAG**

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4*Skift alle 16000 km/ 24 måneder***HYDRAULISK BREMSESYSTEM FOR**

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4*Skift alle 16000 km/ 24 måneder***HYDRAULISK KOBLINGSSYSTEM**

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4*Skift alle 16000 km/ 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.