

KAWASAKI KAF/KAT/KDF (MULE) MULE

2510 KAF 620A (1993-2000)



MOTOR/GEARKASSE

Kapacitet: 1,8 liter, Filterkapacitet: 0,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-50

PRODUKTANBEFALING 2

Expulsa RR 15W-50

PRODUKTANBEFALING 3

Expulsa RR 10W-40

Skift alle 10000 km/ 500 timer/ 12 måneder

DIFFERENTIALE BAG

Kapacitet: 2,5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 10000 km/ 500 timer/ 12 måneder

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

SP Gear 1071

Skift alle 10000 km/ 500 timer/ 12 måneder

DIFFERENTIALE FOR

Kapacitet: 0,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube LS 80W-90

Skift alle 10000 km/ 500 timer/ 12 måneder

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 5000 km/ 250 timer, skift alle 24 måneder

KAWASAKI KAF/KAT/KDF (MULE) MULE

2510 KAF 620A (1993-2000)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 2

MP Lithep Grease EP 2

Kontroller alle 5000 km/ 250 timer

KØLESYSTEM

Kapacitet: 2,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

Kontroller alle 10000 km/ 500 timer, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.