

KAWASAKI KAF/KAT/KDF (MULE) MULE

610 4X4 KAF 400A/C (2005-2013)



MOTOR

Kapacitet: 1,4 liter, Filterkapacitet: 0,55 liter

ANVEND		KLIMA
Normal		Middelhavsgtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

Skift alle 5000 km/ 250 timer/ 12 måneder

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
Expulsa RR 5W-40		

Skift alle 5000 km/ 250 timer/ 12 måneder

ANVEND		KLIMA
Første Service		Middelhavsgtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

Skift alle 1000 km/ 50 timer

ANVEND		KLIMA
Første Service		Arktisk
PRODUKTANBEFALING 1		
Expulsa RR 5W-40		

Skift alle 1000 km/ 50 timer

DIFFERENTIALE FOR

Kapacitet: 0,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube Racing 75W-140		

Skift alle 10000 km/ 500 timer/ 12 måneder

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1		
Gearlube Racing 75W-140		

Skift alle 1000 km/ 50 timer

KAWASAKI KAF/KAT/KDF (MULE) MULE 610 4X4 KAF 400A/C (2005-2013)



GEARKASSE HØJ/LAV 2/1

Kapacitet: 2,4 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 10000 km/ 500 timer/ 12 måneder

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

SP Gear 1071

Skift alle 10000 km/ 500 timer/ 12 måneder

ANVEND

Første Service

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 km/ 50 timer

ANVEND

Første Service

KLIMA

Koldt

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

SP Gear 1071

Skift alle 1000 km/ 50 timer

HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 5000 km/ 250 timer, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.