

KAWASAKI KLF (BAYOU) BAYOU 300 4X4 KLF 300C (1995-2004)



MOTOR/GEARKASSE

Kapacitet: 2,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

Skift alle 3 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

Skift alle 10 timer

DIFFERENTIALE BAG

Kapacitet: 0,2 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 12 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	SP Gear 1071	

Skift alle 12 måneder

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 10 timer

ANVEND	KLIMA
Første Service	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	SP Gear 1071	

Skift alle 10 timer

KAWASAKI KLF (BAYOU) BAYOU 300 4X4 KLF 300C (1995-2004)



DIFFERENTIALE FOR

Kapacitet: 0,25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

Skift alle 12 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

Skift alle 10 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 1 måneder, skift alle 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.