

# KAWASAKI VULCAN / LTD EN / VN VN

## VULCAN 1500 NOMAD FI VN1500-L1 > L5

(2000-2004)



### MOTOR/GEARKASSE

Kapacitet: 3,1 liter (Servicepåfyldning), Kapacitet: 3,5 liter (Tør efterfyld), Filterkapacitet: 0,2 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1     | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3     |
|-------------------------|--------------------------|-------------------------|
| <b>Expulsa RR 5W-50</b> | <b>Expulsa RR 15W-50</b> | <b>Expulsa RR 5W-40</b> |

Skift alle 6000 km/ 6 måneder

| ANVEND         | KLIMA            |
|----------------|------------------|
| Første Service | Middelhavsagtigt |

| PRODUKTANBEFALING 1     | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3     |
|-------------------------|--------------------------|-------------------------|
| <b>Expulsa RR 5W-50</b> | <b>Expulsa RR 15W-50</b> | <b>Expulsa RR 5W-40</b> |

Skift alle 1000 km

### AKSELDREV

Kapacitet: 0,2 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 36000 km

| ANVEND | KLIMA |
|--------|-------|
| Normal | Koldt |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |  |
|---------------------|---------------------|--|
| <b>SP Gear 5015</b> | <b>SP Gear 1071</b> |  |

Skift alle 36000 km

| ANVEND         | KLIMA            |
|----------------|------------------|
| Første Service | Middelhavsagtigt |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 1000 km

| ANVEND         | KLIMA |
|----------------|-------|
| Første Service | Koldt |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |  |
|---------------------|---------------------|--|
| <b>SP Gear 5015</b> | <b>SP Gear 1071</b> |  |

Skift alle 1000 km

# KAWASAKI VULCAN / LTD EN / VN VN

## VULCAN 1500 NOMAD FI VN1500-L1 > L5

(2000-2004)



### HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

PRODUKTANBEFALING 2

**Drauliquid-S DOT 4**

*Skift alle 24000 km/ 24 måneder*

### HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

PRODUKTANBEFALING 2

**Drauliquid-S DOT 4**

*Skift alle 24000 km/ 24 måneder*

### KØLESYSTEM

Kapacitet: 2,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

*Skift alle 24000 km/ 24 måneder*

### FORGAFFEL

Kapacitet: 397 cm3 (hver side)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Fork Oil RR 10**

*Skift alle 24000 km/ 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.