

KAWASAKI W-SERIE EJ650 W650 EJ650-A1

> (1999-2007)



MOTOR/GEARKASSE

Kapacitet: 2,8 liter (Servicepåfyldning), Kapacitet: 3 liter (Tør efterfyld), Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 5W-40

Skift alle 6000 km/ 6 måneder

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 5W-40

Skift alle 1000 km

HYDRAULISK BREMSESYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 6000 km/ 1 måneder, skift alle 24000 km/ 24 måneder

SMØREPUNKTER/NIPLER ANDRE

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Skift alle 24000 km/ 24 måneder

FORGAFFEL

Kapacitet: 379 cm3 (hvert ben)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Fork Oil RR 10		

Skift alle 24000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.