

# KAWASAKI Z-SERIE ZR / ZX Z 650-D4 (SR)

(1981-1981)



## MOTOR/GEARKASSE

Kapacitet: 3,5 liter, Filterkapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Expulsa RR 5W-50**

PRODUKTANBEFALING 2

**Expulsa RR 15W-50**

PRODUKTANBEFALING 3

**Expulsa RR 10W-40**

*Skift alle 5000 km/ 12 måneder*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

**Expulsa RR 5W-50**

PRODUKTANBEFALING 2

**Expulsa RR 15W-50**

PRODUKTANBEFALING 3

**Expulsa RR 10W-40**

*Skift alle 800 km*

## HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid DOT 3**

*Kontroller alle 5000 km/ 1 måneder, skift alle 10000 km/ 12 måneder*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid DOT 3**

*Kontroller alle 800 km*

## SMØREPUNKTER/NIPLER GENERELT

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**HDX 30**

*Skift alle 5000 km*

# KAWASAKI Z-SERIE ZR / ZX Z 650-D4 (SR) (1981-1981)



## FORGAFFEL

Kapacitet: 260 cm3 (hver side)

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Perlus H 32**

*Skift alle 10000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*