

KTM 1290 1290 SUPER DUKE R (2014-2015)



MOTOR/GEARKASSE

Kapacitet: 3,6 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Expulsa RR 5W-50

Skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1

Expulsa RR 5W-50

Skift alle 1000 km

ANVEND	KLIMA
Første Service	Arktisk

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 1000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 5.1

PRODUKTANBEFALING 2

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 3

Drauliquid-S DOT 4

Skift alle 24 måneder

HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KTM 1290 1290 SUPER DUKE R (2014-2015)**KØLESYSTEM**

Kapacitet: 3,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1**Coolant -38 Organic NF***Skift alle 48 måneder***FORGAFFEL WP 4860 ROTA SPLIT**Kapacitet: 660 cm³ (hvert ben)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

STØDDÆMPER BAG WP 4618 BAVP DCC

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.