

KTM 150 150 XC (USA) (2013-2014)



MOTOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Tornado

PRODUKTANBEFALING 2

Maestrol

GEAR 6

Kapacitet: 0,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 15W-50

Skift alle 20 timer/ 140 liter forbrugt brændstof

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 5.1

PRODUKTANBEFALING 2

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 3

Drauliquid-S DOT 4

Skift alle 12 måneder

HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KØLESYSTEM

Kapacitet: 1,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Kontroller alle 20 timer/ 140 liter forbrugt brændstof

FORGAFFEL WP 4860 MXMA CC

Kapacitet: 370 cm³ (hvert ben uden patron), Kapacitet: 195 cm³ (patron hver)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

STØDDÆMPER BAG WP 5018 BAVP DCC

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUKTANBEFALING

KTM 150 150 XC (USA) (2013-2014)



information contained herein is subject to changes without notification.