

KTM 620 / 640 DUKE (II) 640 DUKE II (2003-2003)



MOTOR/GEARKASSE

Kapacitet: 2,1 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Expulsa RR 15W-50

Skift alle 5000 km/ 12 måneder

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Expulsa RR 5W-50

PRODUKTANBEFALING 2

Expulsa RR 10W-40

Skift alle 5000 km/ 12 måneder

ANVEND

Første Service

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Expulsa RR 15W-50

Skift alle 1000 km

ANVEND

Første Service

KLIMA

Arktisk

PRODUKTANBEFALING 1

Expulsa RR 5W-50

PRODUKTANBEFALING 2

Expulsa RR 10W-40

Skift alle 1000 km

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 5.1

PRODUKTANBEFALING 2

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 3

Drauliquid-S DOT 4

Kontroller alle 5000 km, skift alle 12 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 5.1

PRODUKTANBEFALING 2

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 3

Drauliquid-S DOT 4

Kontroller alle 1000 km

KTM 620 / 640 DUKE (II) 640 DUKE II (2003-2003)



KØLESYSTEM

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.