

**MOTOR/GEARKASSE**

Kapacitet: 1,7 liter

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Expulsa RR 5W-40*Skift alle 15 timer/ 100 liter forbrugt brændstof/ 1 løb*

ANVEND

Første Service

KLIMA

Arktisk

PRODUKTANBEFALING 1

Expulsa RR 5W-40*Skift alle 1 timer/ 7 liter forbrugt brændstof***HYDRAULISK BREMSESYSTEM**

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 5.1

PRODUKTANBEFALING 2

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 3

Drauliquid-S DOT 4*Skift alle 12 måneder***HYDRAULISK KOBLINGSSYSTEM**

Kapacitet: 0-0 liter (Imellem min. og max.)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KØLESYSTEM

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 1 løb/ 100 liter forbrugt brændstof/ 15 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.