

KYMCO K-XCT K-XCT 300I (2012 OG EFTER)



MOTOR SK60B
Kapacitet: 1,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Expulsa RR 10W-40	Expulsa 10W-40	

Kontroller alle 500 km, skift alle 4000 km

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Expulsa RR 10W-40	Expulsa 10W-40	

Skift alle 300 km

SLUT-REDUKTION
Kapacitet: 210 cm³

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear 75W-90	

Kontroller alle 4000 km, skift alle 8000 km

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear 75W-90	

Skift alle 300 km

HYDRAULISK BREMSESYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid DOT 5.1		

Skift alle 24 måneder

KYMCO K-XCT K-XCT 300I (2012 OG EFTER)

**KØLESYSTEM**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Skift alle 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.