

# LINHAI CUV / REBEL LH 300 CUV 4X2



**MOTOR** 173MM  
Kapacitet: 1,4 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Expulsa RR 10W-40**

*Skift alle 3 måneder/ 30 timer*

## GEARKASSE HØJ/LAV 2/1

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 100 timer/ 12 måneder*

## SLUT-REDUKTION

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 100 timer/ 12 måneder*

## HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Drauliquid DOT 3**

*Skift alle 24 måneder/ 200 timer*

## KØLESYSTEM

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

PRODUKTANBEFALING 2

**Coolant -26**

*Skift alle 12 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.