

PEUGEOT TWEET TWEET 125 LW2A (2010-2017)



MOTOR XS1P52QMI-4

Kapacitet: 0,7 liter (Servicepåfyldning), Kapacitet: 0,95 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 2000 km/ 6 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 1000 km/ 6 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 500 km/ 1 måneder

SLUT-REDUKTION

Kapacitet: 0,18 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 5000 km/ 48 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 2500 km/ 24 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 500 km/ 1 måneder

PEUGEOT TWEET TWEET 125 LW2A (2010-2017)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 24 måneder

FORGAFFEL

Kapacitet: 100 cm³ (hvert ben)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Fork Oil RR 10		

Skift alle 20000 km/ 48 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
Fork Oil RR 10		

Skift alle 10000 km/ 48 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.