



## MOTOR

Kapacitet: 0,8 liter (Servicepåfyldning), Kapacitet: 0,9 liter (Tør efterfyld)

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Expulsa RR 10W-40**

#### PRODUKTANBEFALING 2

**HDX 15W-40**

Skift alle 1000 km

## DIFFERENTIALE BAG

Kapacitet: 0,3 liter (Servicepåfyldning), Kapacitet: 0,33 liter (Tør efterfyld)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

## NAVREDUKTIONER

Kapacitet: 0,09 liter (Servicepåfyldning), Kapacitet: 0,11 liter (Tør efterfyld)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

## HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Drauliquid DOT 3**

Skift alle 24 måneder

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*