

PGO X-HOT X-HOT 125 BF2-125 (2008 OG EFTER)



MOTOR

Kapacitet: 0,8 liter (Servicepåfyldning), Kapacitet: 1 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Expulsa RR 10W-40	HDX 15W-40	

Skift alle 1000 km

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Expulsa RR 10W-40	HDX 15W-40	

Skift alle 300 km/ 1 måneder

NAVREDUKTIONER

Kapacitet: 0,09 liter (Servicepåfyldning), Kapacitet: 0,11 liter (Tør efterfyld)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Skift alle 24 måneder

FORGAFFEL

Kapacitet: 84 cm³ (hvert ben)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.