



MOTOR M713M
Kapacitet: 1,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Expulsa RR 5W-40

Kontroller alle 5000 km/ 10 måneder, skift alle 10000 km/ 20 måneder

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Expulsa RR 5W-40

Skift alle 1000 km

NAVREDUKTIONER
Kapacitet: 150 cm³

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 5015

PRODUKTANBEFALING 2
Gearlube GL-4 80W

Kontroller alle 10000 km/ 20 måneder, skift alle 20000 km/ 40 måneder

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 5015

PRODUKTANBEFALING 2
Gearlube GL-4 80W

Skift alle 1000 km

HYDRAULISK BREMSESYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

Skift alle 10000 km/ 20 måneder

**KØLESYSTEM**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 5000 km, skift alle 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.