

RIEJU RS2 RS2 50 MATRIX (2006-2011)



MOTOR + AUTOMATISK SMØRING Minarelli AM6

Kapacitet: 1,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Tornado	Scoosynth	Maestrol

GEAR 6

Kapacitet: 0,82 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Expulsa RR 10W-40	Expulsa 10W-40	

Skift alle 3000 km

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Expulsa RR 10W-40	Expulsa 10W-40	

Skift alle 500 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

KØLESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

RIEJU RS2 RS2 50 MATRIX (2006-2011)



FORGAFFEL Paioli Kapacitet: 380 cm ³		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Fork Oil RR 10		

FORGAFFEL Showa Kapacitet: 210 cm ³		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Fork Oil RR 10		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.