

# SKI-DOO EXPEDITION EXPEDITION SE 900 ACE (2015-2016)



**MOTOR** Rotax 903  
Kapacitet: 3,3 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Helar 0W-40**

*Kontroller alle 500 km/ 10 timer, skift alle 6000 km/ 12 måneder*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

PRODUKTANBEFALING 1

**Helar 0W-40**

*Skift alle 500 km/ 10 timer*

| ANVEND          | KLIMA   |
|-----------------|---------|
| Andet skift kun | Moderat |

PRODUKTANBEFALING 1

**Helar 0W-40**

*Skift alle 3000 km/ 12 måneder*

**GEARKASSE** 2/1  
Kapacitet: 0,7 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Gearlube Racing 75W-140**

*Kontroller alle 1500 km, skift alle 12 måneder*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

PRODUKTANBEFALING 1

**Gearlube Racing 75W-140**

*Skift alle 500 km/ 10 timer*

# SKI-DOO EXPEDITION EXPEDITION SE 900 ACE (2015-2016)



## HYDRAULISK BREMSESYSTEM

| ANVEND                           |                           | KLIMA   |
|----------------------------------|---------------------------|---------|
| Normal                           |                           | Moderat |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |         |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |         |

Kontroller alle 12 måneder, skift alle 6000 km/ 24 måneder

| ANVEND                           |                           | KLIMA   |
|----------------------------------|---------------------------|---------|
| Første Service                   |                           | Moderat |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |         |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |         |

Kontroller alle 500 km/ 10 timer

## KØLESYSTEM

| ANVEND                |                      | KLIMA                         |
|-----------------------|----------------------|-------------------------------|
| Normal                |                      | Moderat                       |
| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2  | PRODUKTANBEFALING 3           |
| <b>Coolant SP 15+</b> | <b>Coolant SP 12</b> | <b>Coolant -38 Organic NF</b> |

Skift alle 60 måneder

| ANVEND                |                      | KLIMA                         |
|-----------------------|----------------------|-------------------------------|
| Første Service        |                      | Moderat                       |
| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2  | PRODUKTANBEFALING 3           |
| <b>Coolant SP 15+</b> | <b>Coolant SP 12</b> | <b>Coolant -38 Organic NF</b> |

Kontroller alle 500 km/ 10 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.