

SKI-DOO SUMMIT SUMMIT 500 SS (2009-2010)



MOTOR + AUTOMATISK SMØRING Rotax 593
Kapacitet: 3,7 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

HYDRAULISK BREMSESYSTEM
Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

Kontroller alle 12 måneder, skift alle 6000 km/ 24 måneder

KØLESYSTEM
Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant SP 15+

PRODUKTANBEFALING 2
Coolant SP 12

PRODUKTANBEFALING 3
Coolant -38 Organic NF

Kontroller alle 12 måneder, skift alle 6000 km/ 24 måneder

KÆDEKASSE
Kapacitet: 0-0 liter (Imellem min. og max.)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.