

SUZUKI DL V-STROM DL1000A V-STROM (2013-2020)



MOTOR/GEARKASSE

Kapacitet: 3,1 liter (Servicepåfyldning), Kapacitet: 3,5 liter (Tør efterfyld), Filterkapacitet: 0,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-50

PRODUKTANBEFALING 2

Expulsa RR 15W-50

PRODUKTANBEFALING 3

Expulsa RR 10W-40

Skift alle 12000 km/ 12 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-50

PRODUKTANBEFALING 2

Expulsa RR 15W-50

PRODUKTANBEFALING 3

Expulsa RR 10W-40

Skift alle 1000 km/ 2 måneder

HYDRAULISK BREMSESYSTEM ABS

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 6000 km/ 12 måneder, skift alle 24 måneder

HYDRAULISK KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 12000 km/ 12 måneder, skift alle 24 måneder

SUZUKI DL V-STROM DL1000A V-STROM (2013-2020)



KØLESYSTEM

Kapacitet: 2,13 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Skift alle 48000 km/ 48 måneder

ANVEND

Normal (alternativ)

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

PRODUKTANBEFALING 2

Coolant -38 Organic NF

Skift alle 24000 km/ 24 måneder

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Skift alle 24000 km/ 24 måneder

FORGAFFEL

Kapacitet: 569 cm³ (hvert ben)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.