

SUZUKI GS GS 500 /F (2004-2009)



MOTOR/GEARKASSE

Kapacitet: 2,9 liter (Servicepåfyldning), Kapacitet: 3,2 liter (Tør efterfyld), Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 6000 km/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-50

PRODUKTANBEFALING 2

Expulsa RR 15W-50

PRODUKTANBEFALING 3

Expulsa RR 5W-40

Skift alle 6000 km/ 12 måneder

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 1000 km/ 2 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-50

PRODUKTANBEFALING 2

Expulsa RR 15W-50

PRODUKTANBEFALING 3

Expulsa RR 5W-40

Skift alle 1000 km/ 2 måneder

HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 6000 km, skift alle 24 måneder

FORGAFFEL

Kapacitet: 380 cm3 (hvert)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.