

SUZUKI LT LT-A 400 EIGER/KINGQUAD 4X2 (2004-2009)



MOTOR

Kapacitet: 3,1 liter (Servicepåfyldning), Kapacitet: 3,4 liter (Tør efterfyld), Filterkapacitet: 0,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-40

PRODUKTANBEFALING 2

Expulsa RR 10W-40

PRODUKTANBEFALING 3

Expulsa 10W-40

Skift alle 2000 km/ 6 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-40

PRODUKTANBEFALING 2

Expulsa RR 10W-40

PRODUKTANBEFALING 3

Expulsa 10W-40

Skift alle 200 km/ 1 måneder

GEARKASSE HØJ/LAV 2/1

Kapacitet: 0,35 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 2000 km/ 6 måneder, skift alle 24 måneder

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 1000 km/ 3 måneder, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.