

SUZUKI RM(-Z) RM 125 K5 (2005-2005)



MOTOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Tornado

PRODUKTANBEFALING 2

Scoosynth

PRODUKTANBEFALING 3

Maestrol

GEAR 6

Kapacitet: 0,75 liter (Servicepåfyldning), Kapacitet: 0,8 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-40

PRODUKTANBEFALING 2

Expulsa RR 10W-40

PRODUKTANBEFALING 3

Expulsa 10W-40

Skift alle 3 løb/ 6 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 1 løb/ 2 timer, skift alle 12 måneder

KØLESYSTEM

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Kontroller alle 1 løb/ 2 timer, skift alle 12 måneder

FORGAFFEL

Kapacitet: 193 cm³ (Indre rør), Kapacitet: 352 cm³ (Ydre rør)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

STØDDÆMPER BAG

Kapacitet: 380 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.