

SUZUKI RV (VANVAN) RV 125 VANVAN (2003-2016)



MOTOR/GEARKASSE

Kapacitet: 0,95 liter (Servicepåfyldning), Kapacitet: 1,2 liter (Tør efterfyld), Filterkapacitet: 0,1 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 4000 km/ 20 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-50

PRODUKTANBEFALING 2

Expulsa RR 15W-50

PRODUKTANBEFALING 3

Expulsa RR 5W-40

Skift alle 4000 km/ 20 måneder

ANVEND

Første Service

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 1000 km/ 5 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-50

PRODUKTANBEFALING 2

Expulsa RR 15W-50

PRODUKTANBEFALING 3

Expulsa RR 5W-40

Skift alle 1000 km/ 5 måneder

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 4000 km/ 20 måneder, skift alle 24 måneder

FORGAFFEL

Kapacitet: 230 cm³ (hvert)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.