

SUZUKI UX 125/150 SIXTEEN UX 150 SIXTEEN (2008-2019)



MOTOR

Kapacitet: 1,2 liter (Servicepåfyldning), Kapacitet: 1,4 liter (Tør efterfyld), Filterkapacitet: 0,1 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Expulsa RR 5W-50

PRODUKTANBEFALING 2

Expulsa RR 15W-50

PRODUKTANBEFALING 3

Expulsa RR 5W-40

Skift alle 4000 km/ 20 måneder

ANVEND

Første Service

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Expulsa RR 5W-50

PRODUKTANBEFALING 2

Expulsa RR 15W-50

PRODUKTANBEFALING 3

Expulsa RR 5W-40

Skift alle 1000 km/ 5 måneder

SLUT-REDUKTION

Kapacitet: 0,15 liter (Servicepåfyldning), Kapacitet: 0,16 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-40

PRODUKTANBEFALING 2

Expulsa RR 10W-40

PRODUKTANBEFALING 3

Expulsa 10W-40

Kontroller alle 8000 km/ 40 måneder

HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 24 måneder

KØLESYSTEM

Kapacitet: 1,3 liter (Motor kun), Kapacitet: 0,25 liter (Tank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Skift alle 24 måneder

FORGAFFEL

Kapacitet: 112 cm³ (hvert)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

PRODUKTANBEFALING

SUZUKI UX 125/150 SIXTEEN UX 150 SIXTEEN (2008-2019)



inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.