

SYM EURO MX HS EURO MX 125 HS12W (2003-2007)



MOTOR

Kapacitet: 0,8 liter (Servicepåfyldning), Kapacitet: 1,05 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 10W-40

PRODUKTANBEFALING 2

Expulsa 10W-40

Skift alle 3000 km

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 10W-40

PRODUKTANBEFALING 2

Expulsa 10W-40

Skift alle 300 km

SLUTGEAR

Kapacitet: 0,1 liter (Servicepåfyldning), Kapacitet: 0,11 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

Skift alle 5000 km/ 5 måneder

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 5000 km/ 5 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

Skift alle 300 km

ANVEND

Første Service

KLIMA

Arktisk

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 300 km

SYM EURO MX HS EURO MX 125 HS12W (2003-2007)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.