

SYM MAXSYM MAXSYM 400I ABS (2012-2019)



MOTOR LX40A2-6

Kapacitet: 1,9 liter (Servicepåfyldning), Kapacitet: 2 liter (Tør efterfyld), Filterkapacitet: 0,1 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Expulsa RR 10W-40	Expulsa 10W-40	

Kontroller alle 1000 km/ 1 måneder, skift alle 5000 km/ 3 måneder

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Expulsa RR 10W-40	Expulsa 10W-40	

Skift alle 1000 km/ 1 måneder

SLUTGEAR

Kapacitet: 0,35 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube GL-5 85W-140		

Skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Gearlube GL-5 85W-140		

Skift alle 1000 km/ 1 måneder

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Skift alle 30000 km/ 24 måneder

SYM MAXSYM MAXSYM 400I ABS (2012-2019)



KØLESYSTEM

Kapacitet: 0,45 liter (Ekspansionsbeholder), Kapacitet: 0,65 liter (Radiator)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 15000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.