

TGB TARGET TARGET 425 (2009-2012)



MOTOR

Kapacitet: 3,2 liter (Servicepåfyldning), Kapacitet: 3,5 liter (Tør efterfyld), Filterkapacitet: 0,2 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Expulsa RR 15W-50	Bi-Turbo 20W-50

Skift alle 2000 km

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Expulsa RR 10W-40	Expulsa 10W-40

Skift alle 2000 km

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Expulsa RR 15W-50	Bi-Turbo 20W-50

Skift alle 200 km

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Expulsa RR 10W-40	Expulsa 10W-40

Skift alle 200 km

DIFFERENTIALE

Kapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 24 måneder

SLUTDREV

Kapacitet: 0,35 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 24 måneder

TGB TARGET TARGET 425 (2009-2012)



HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Skift alle 24 måneder

KØLESYSTEM

Kapacitet: 2,2 liter (Radiator + motor), Kapacitet: 1,2 liter (Tank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.