

TRIUMPH SPEED TRIPLE SPEED TRIPLE 1050 R (2012-2015)



MOTOR/GEARKASSE

Kapacitet: 3,2 liter (Servicepåfyldning), Kapacitet: 3,5 liter (Tør efterfyld), Filterkapacitet: 0,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 5W-50	Expulsa RR 5W-40	Expulsa RR 10W-40

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 5W-50	Expulsa RR 5W-40	Expulsa RR 10W-40

Skift alle 800 km/ 1 måneder

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 20000 km/ 24 måneder

SMØREPUNKTER/NIPLER GENERELT

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

KØLESYSTEM

Kapacitet: 2,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Coolant SP 12 EVO		

Skift alle 20000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.