

URAL URAL CT URAL CT CT / T (2014-2015)



MOTOR

Kapacitet: 2,1 liter (Servicepåfyldning)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Expulsa RR 15W-50	Bi-Turbo 20W-50

Skift alle 5000 km/ 12 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	
Expulsa RR 5W-40	

Skift alle 5000 km/ 12 måneder

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Expulsa RR 15W-50	Bi-Turbo 20W-50

Skift alle 1000 km

ANVEND	KLIMA
Første Service	Koldt

PRODUKTANBEFALING 1	
Expulsa RR 5W-40	

Skift alle 1000 km

AKSELDREV

Kapacitet: 110 cm³

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Kontroller alle 5000 km, skift alle 10000 km

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 km



GEAR 4/1
Kapacitet: 0,9 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Expulsa RR 15W-50	Bi-Turbo 20W-50	

Kontroller alle 5000 km, skift alle 10000 km

ANVEND		KLIMA
Normal		Koldt
PRODUKTANBEFALING 1		
Expulsa RR 5W-40		

Kontroller alle 5000 km, skift alle 10000 km

ANVEND		KLIMA
Første Service		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Expulsa RR 15W-50	Bi-Turbo 20W-50	

Skift alle 1000 km

ANVEND		KLIMA
Første Service		Koldt
PRODUKTANBEFALING 1		
Expulsa RR 5W-40		

Skift alle 1000 km

HYDRAULISK BREMSESYSYSTEM

Kapacitet: 15 cm³ (Bag), Kapacitet: 20 cm³ (For), Kapacitet: 0-0 liter (Imellem min. og max.), Kapacitet: 30 cm³ (Passagerside)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Kontroller alle 5000 km, skift alle 30000 km/ 12 måneder

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Kontroller alle 1000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.