

# YAMAHA (USA) XV XV 19 STRATOLINER MIDNIGHT (2008-2009)

**MOTOR/GEARKASSE**

Kapacitet: 4,9 liter, Filterkapacitet: 0,8 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Expulsa RR 15W-50***Skift alle 4000 mil/ 6 måneder*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

PRODUKTANBEFALING 1

**Expulsa RR 15W-50***Skift alle 600 mil/ 1 måneder***SLUTDREV**

Kapacitet: 0,55 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**SP Gear 5015**

PRODUKTANBEFALING 2

**Gearlube GL-4 80W***Kontroller alle 8000 mil/ 12 måneder, skift alle 16000 mil/ 24 måneder*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

PRODUKTANBEFALING 1

**SP Gear 5015**

PRODUKTANBEFALING 2

**Gearlube GL-4 80W***Skift alle 600 mil/ 1 måneder***HYDRAULISK BREMSESYSTEM**

Kapacitet: 0-0 liter (Imellem min. og max.)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

PRODUKTANBEFALING 2

**Drauliquid-S DOT 4***Skift alle 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.