

YAMAHA (USA) YFM BIG BEAR YFM 350 BIG BEAR 2X4 (1998-2000)



MOTOR/GEARKASSE

Kapacitet: 2,8 liter (Servicepåfyldning), Kapacitet: 3,2 liter (Tør efterfyld), Filterkapacitet: 0,4 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Expulsa 10W-40

Skift alle 6 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 6 måneder

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1

Expulsa 10W-40

Skift alle 1 måneder

ANVEND	KLIMA
Første Service	Arktisk

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 1 måneder

SLUTGEAR

Kapacitet: 0,19 liter (Servicepåfyldning), Kapacitet: 0,25 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Skift alle 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Skift alle 1 måneder

YAMAHA (USA) YFM BIG BEAR YFM 350 BIG BEAR 2X4 (1998-2000)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.