

YAMAHA (USA) YFM GRIZZLY YFM 30 GRIZZLY 300 YFM30GD (2012-2014)



MOTOR

Kapacitet: 1,2 liter

ANVEND		KLIMA
Normal		Middelhavsgtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40

Skift alle 1600 mil/ 6 måneder/ 160 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
Expulsa RR 5W-40		

Skift alle 1600 mil/ 6 måneder/ 160 timer

ANVEND		KLIMA
Første Service		Middelhavsgtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40

Skift alle 200 mil/ 1 måneder/ 20 timer

ANVEND		KLIMA
Første Service		Arktisk
PRODUKTANBEFALING 1		
Expulsa RR 5W-40		

Skift alle 200 mil/ 1 måneder/ 20 timer

GEAR AUTOMATISK 1

Kapacitet: 1,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 3200 mil/ 12 måneder/ 320 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 200 mil/ 1 måneder/ 20 timer

YAMAHA (USA) YFM GRIZZLY YFM 30 GRIZZLY 300 YFM30GD (2012-2014)

**SLUTGEAR**

Kapacitet: 0,15 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube GL-4 80W	

Skift alle 3200 mil/ 12 måneder/ 320 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube GL-4 80W	

Skift alle 200 mil/ 1 måneder/ 20 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 24 måneder

KØLESYSTEM

Kapacitet: 1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.