

YAMAHA (USA) YFM GRIZZLY YFM 35 GRIZZLY 350 4X4 YFM35FGD (2013-2014)



MOTOR

Kapacitet: 2,3 liter, Filterkapacitet: 0,1 liter

ANVEND

Normal

KLIMA

Middelhavssagtigt

PRODUKTANBEFALING 1

Expulsa RR 15W-50

PRODUKTANBEFALING 2

Expulsa RR 10W-40

PRODUKTANBEFALING 3

Expulsa 10W-40

Skift alle 1600 mil/ 6 måneder/ 160 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 1600 mil/ 6 måneder/ 160 timer

ANVEND

Første Service

KLIMA

Middelhavssagtigt

PRODUKTANBEFALING 1

Expulsa RR 15W-50

PRODUKTANBEFALING 2

Expulsa RR 10W-40

PRODUKTANBEFALING 3

Expulsa 10W-40

Skift alle 200 mil/ 1 måneder/ 20 timer

ANVEND

Første Service

KLIMA

Arktisk

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 200 mil/ 1 måneder/ 20 timer

DIFFERENTIALE BAG

Kapacitet: 0,35 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Skift alle 3200 mil/ 12 måneder/ 320 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Skift alle 200 mil/ 1 måneder/ 20 timer

YAMAHA (USA) YFM GRIZZLY YFM 35 GRIZZLY 350 4X4 YFM35FGD (2013-2014)



SLUTGEAR

Kapacitet: 0,23 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Skift alle 3200 mil/ 12 måneder/ 320 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Skift alle 200 mil/ 1 måneder/ 20 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.