

YAMAHA (USA) YJ VINO YJ 125 VINO (2004-2005)



MOTOR

Kapacitet: 1 liter (Servicepåfyldning), Kapacitet: 1,2 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 15W-50	HDX 15W-40	HDX 20W-50

Skift alle 2000 mil/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40

Skift alle 2000 mil/ 6 måneder

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 15W-50	HDX 15W-40	HDX 20W-50

Skift alle 600 mil/ 1 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40

Skift alle 600 mil/ 1 måneder

NAVREDUKTIONER BAG

Kapacitet: 0,13 liter (Servicepåfyldning), Kapacitet: 0,15 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube GL-5 85W-140		

Skift alle 4000 mil/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Gearlube GL-5 85W-140		

Skift alle 600 mil/ 1 måneder

YAMAHA (USA) YJ VINO YJ 125 VINO (2004-2005)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.