



MOTOR + AUTOMATISK SMØRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Tornado	Scoosynth	Maestrol

GEAR 5

Kapacitet: 0,8 liter (Servicepåfyldning), Kapacitet: 0,75 liter (Tør efterfyld)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Expulsa RR 10W-40	Expulsa 10W-40	

Kontroller alle 3 timer/ 1 løb, skift alle 13 timer/ 5 løb

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 3 timer/ 1 løb, skift alle 12 måneder

KØLESYSTEM

Kapacitet: 1,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

Kontroller alle 1 løb, skift alle 24 måneder

FORGAFFEL

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 32		

Kontroller alle 3 timer/ 1 løb, skift alle 13 timer/ 5 løb

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.